

GreenSEAL G Drain Tanking Drainage Protection



T-Kone G DRAIN

GreenSEAL Tanking Protection

Year of last update: 2017

Reference norms: EN 13252

Certificate number: 1213-CPD-4006

Function: Tanking Protection



STRUCTURE: HDPE Studded Membrane Bonded to Geotextile for Mechanical Protection of Waterproofing Membranes

FILTER GEOTEXTILES

Raw material			PP
Total Weight	EN ISO 9864	g/m ²	600
Thickness	EN ISO 9863-1	mm	8.00
Compression Resistance	EN ISO		200
Tensile Strength	EN ISO 10319	Kn/m	10/10
Elongation MD/CMD	EN ISO 10319	%	50/50
Drainflow – Horizontal Application (M/R, 20kPa, i=0,04)	EN ISO 12958		0.25
Drainflow – Vertical Application (M/R, 20kPa, i=0,04)	EN ISO 12958		1.75

PACKAGE DIMENSIONS

Roll Length	M	20.0
Roll Width	M	2.0
Rolls Per Pallet	EA	6

The information given in this data sheet is to the best of our knowledge true and correct. Sealco reserves the right to change its product specifications at any time. It is the responsibility of the specifier and purchaser to ensure that product specifications used for design and procurement purposes are current and consistent with the products used in each instance.

Sealco Waterproofing Systems
31 Newtown Street
Bromley
Christchurch
(0508) SEALCO
www.sealco.co.nz



REV. 1/2017